



## Fibox JB Junction Box

Fibox JB electrical junction boxes are designed for indoor and outdoor use.

Enclosures are maintenance free and corrosion resistant.

Aesthetic design maximizing installation space – easy installation.

Membrane entries allow flexible cable entry options.

- Snap-on cover, JB 6 cover can be screwed on if necessary
- High protection degree IP65
- Flexible membrane entries make cutting and breaking unnecessary
- Wires, cables and conduits (with max Dia 20 mm) can be inserted directly
- Cable glands can be screwed directly into the entries without any couplings or locknut being necessary
- Material Polypropylene



## Fibox JB Junction Box

Order symbol	Code	Dimensions mm	EAN	Pack	Description
<b>Junction box 2,5 mm<sup>2</sup></b>					
JB 2,5 G	8600670	90 x 90 x 49	6418074307859	10/100	grey RAL 7035
JB 2,5 WH	8600671	90 x 90 x 49	6418074308566	10/100	white RAL 9010
<b>Junction box 6 mm<sup>2</sup></b>					
JB 6 G	8600672	110 x 110 x 49	6418074307866	10/100	grey RAL 7035
JB 6 WH	8600673	110 x 110 x 49	6418074308573	10/100	white RAL 9010




JB 2,5



JB 6

## Accessories

Order symbol	Code	EAN	Pack	Description
<b>Accessories for JB 2,5 mm<sup>2</sup> and 6 mm<sup>2</sup></b>				
ITS 6	8600650	6418074079091	20/200	Terminal strip for JB 2,5 and JB 6 6 mm <sup>2</sup> - 500V - hole-type 5-terminal strip Possible connections per terminal: 6 x 1.5 mm <sup>2</sup> 3 x 4 mm <sup>2</sup> 4 x 2.5 mm <sup>2</sup> 2 x 6 mm <sup>2</sup>
<b>Accessories for JB 6 mm<sup>2</sup></b>				
IES	8600346	6418074079077	25	Tube entry socket for JB 6 M20 grey for tube ø 16 mm for tube ø 20 mm
ICS	8600652	6418074079084	40	Cover fastening screws for JB 6 Stainless steel
GPA M20	7016402	6418074054869	100	Cable gland for JB 6, IP68 for cables 8 - 13 mm
GPA M20R	7016781	6418074091239	100	Cable gland for JB 6, IP68 Double seal cable gland for cables 5 - 13 mm



ITS 6



IES



ICS



GPA M20



GPA M20R

### Technical information

Property	Polypropylene (PP)
Ingress Protection (EN 60529)	IP 65
Impact Resistance (EN 62262)	IK 04
Temperature Range Celsius	-5° . . .60°C
Temperature Range Fahrenheit	23° . . .160°F
Electrical Insulation	Totally insulated ☑
Color	RAL 7035 or RAL 9010
Gasket	TPE
Membrane	TPE
Glow Wire Test (IEC 695-2-1)	650°C
Non -toxicity	Halogen Free
Chemical Resistance *	Good

### Conformity to standards

**Europe**  
**EN 60670** Boxes and Enclosures for electrical accessories for household and similar fixed electrical installations

RoHS directive 2011/65/EU

Data subject to change without notice.

\*\*Consult separate raw material data for more detailed information

[www.fibox.com](http://www.fibox.com)



**Fibox Oy Ab**  
Keilaranta 19 D  
FI-02150 Espoo  
Finland

Tel. +358 (0)207 785 700  
Fax +358 (0)207 785 702  
E-mail: [info@fibox.fi](mailto:info@fibox.fi)  
Homepage: [www.fibox.com](http://www.fibox.com)

code: 9637215

