

# Cat5e & Cat6 Network Cables

Fluke Tested

# Labgear



## 70400LS

**Cat6 UTP Interior Cable  
23AWG Low Smoke (LSZH)  
4 Twisted Pairs 305m**

- Interior cable
- Fast feed reflex packaging
- Category 6 Compliant
- CPR Compliant to ECA
- 1000Base-T Compatible

### Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **23AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 250MHz  
Enhanced test 500MHz**



## 70400R

**Cat6 UTP Interior Cable  
23AWG 4 Twisted Pairs 305m**

- Interior cable
- Fast feed reflex packaging
- Category 6 Compliant
- CPR Compliant to ECA
- 1000Base-T Compatible

### Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **23AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 250MHz  
Enhanced test 500MHz**



## 70400PE

**Cat6 UTP Exterior Cable  
23AWG 4 Twisted Pairs 305m**

- Exterior weatherproof cable
- Fast feed reflex packaging
- Category 6 Compliant
- UV Resistant
- 1000Base-T Compatible

### Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **23AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **250MHz**



## 70399R

**Cat5e UTP Interior Cable  
24AWG 4 Twisted Pairs 305m**

- Interior cable
- Fast feed reflex packaging
- Category 5e Compliant
- CPR Compliant to ECA
- 100Base-T Compatible

### Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **24AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 100MHz  
Enhanced test 350MHz**



## 70399PE

**Cat5e UTP Exterior Cable  
24AWG 4 Twisted Pairs 305m**

- Exterior weatherproof cable
- Fast feed reflex packaging
- Category 5e Compliant
- UV Resistant
- 100Base-T Compatible

### Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **24AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 100MHz  
Enhanced test 350MHz**