

# IC-HVD100

## SPECIFICATIONS

Inputs	16 x BNC (HDCVI, CVBS, HDTV & AHD)
Outputs	32 x BNC (HDCVI, CVBS, HDTV & AHD)
Application Humidity	-
Power	100-240V AC
Power Consumption	≤2W
Operating temperature	-10°C -55°C
Weight	2.78kg
Dimension	440mm×200mm×43.65mm

## FEATURES

- 16 x BNC Input / 32 BNC Output, each BNC input has two BNC outputs
- BNC's work with HDCVI, HDTV, AHD & CVBS
- Supports the following HDCVI Video Formats  
720P/25  
720P/30  
720P/50  
720P/60  
1080P/25  
1080P/30
- Enterprise level metal design (19" 1U)



Email us [info@icrealtime.net](mailto:info@icrealtime.net) or visit [www.icrealtime.net](http://www.icrealtime.net)

• **European Head Office**  
• IC Realtime,  
• 12 Knockmitten Lane,  
• Western Industrial Estate,  
• Dublin 12,  
• Ireland

• **UK Office**  
• IC Realtime UK  
• Surrey Technology Centre,  
• 40 Occam Road,  
• Guildford GU2 7YG,  
• United Kingdom

• **USA Head Office**  
• IC Realtime, LLC,  
• 3050 N Andrews Ave EXT,  
• Pompano Beach,  
• FL 33064,  
• USA

• **USA West Coast Office**  
• IC Realtime West Coast,  
• 14180 W Van Buren Street,  
• Suite B-105, Goodyear,  
• AZ 85338,  
• USA