

IC-RG-59+2

- 250m of High Quality RG-59+2 Cable
- High Quality Bare Copper Core for increased distance
- Compatible with HD over Coax technologies like HD-CVI, HD-TVI and AHD
- Compatible with SD CVBS Analogue transmission
- Supplied in Wooden Drum

SPECIFICATIONS

Inner Conductor	0.643mm Bare Copper
Dielectric	3.8±0.05mm Solid PE
Shield	Aluminium Foil+128N/0.12CCA
Jacket	6.00±0.1mm PVC
Power Conductor	16×0.2mm Bare Copper
Diameter of PWR Insulation	2.05mm PVC
Power Colour Code	Red & Black
Jacket	5.4±0.1mm PVC
Capacitance	67±2 pF/m
Impedance	75±3 Ω
Inner Conductor Resistance	65.26 Ohms/KM at 20°C
Return Loss	Between 5 and 1000MHz: > 22dB
Velocity of Propagation	0.66
Sparker Test (VAC)	3
Operating Temp Range	-20 °C to 70°C (PVC)
RoHS	Yes



Email us info@icrealtime.net or visit www.icrealtime.net

Specifications subject to change without notice. ©2018 IC Realtime Limited. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.