Electronic Locking Magnet Range




۹



Standard Magnetic Locks (1200lb)

Technical specifications

- Aluminium housing.
- 12/24VDC @600/300mA.
- 545kgs (1200lb) holding force.
- Built in surge protection.
- ML1200-M = Monitored



| ML1200 / ML1200-M | 267x73x40 (mm) | Magnetic Lock (1200lb / 545kg) | 4.27Kg (Boxed) / 2.79Kg (Unboxed) |
|-------------------|----------------|--------------------------------|-----------------------------------|
| Armature Plate | 185x60x15 (mm) | Armature Plate | 1.26Kg (Unboxed) |
| BK1200ZL | Z = 266L (mm) | ZL Bracket | 1.26Kg (Boxed) / 1.12Kg (Unboxed) |
| BK1200L | L = 185L (mm) | L Bracket | 524g (Boxed) / 426g (Unboxed) |

Other items in the RGL range.



FIRE TESTED

The ML600 range of magnets and brackets have been fire tested to BSEN1634-1-2014

(30 & 60 minute timber door-sets)

FEATURES

- Standard magnet.
- Clean and compact design in aluminium.
- Single LED indication ML1200.
- Multi LED indication ML1200-M

Suitable brackets:

- BK1200ZL (ZL bracket)
- BK1200L (L bracket)
- AH1200 (Armature Housing)

